



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**


	Date :	Nov 25, 2025
	PR No. :	2025-09-01529
	Address	

Please quote your lowest price on the item/s listed below and submit your quotation duly signed by your representative not later than **Tuesday, December 2, 2025 10:00 AM** at **CGSO Building, City Civic Center, Alasas, City of San Fernando, Pampanga**.

Canvassed by:

Approved by:

Ana Liza C. Zablan
Administrative Assistant III (Buyer III)


Engr. Michael N. Quizon, Jr.
BAC Chairperson

- NOTE:
1. ALL ENTRIES MUST BE READABLE
 2. DELIVERY PERIOD WITHIN _____ CALENDAR DAYS
 3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY
 4. PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
1	1	unit(s)	Brand New High Roof Ambulance Overall (LxWxH): 5,915 x 1,950 x 2,280 mm Wheelbase:3860mm Engine Type: 2.8L, 4 Cylinders, In-line Type 16-Valve DOHC Engine Displacement: 2755cc Maximum Output: 163ps / 3,600rpm Maximum Torque: 420Nm / 1,400 – 2,200 rpm Transmission: Dash Mounted, AT Fuel Capacity: 70L Tires: 235 / 65 R16C Wheels: 7J x 16” (Alloy) Fully customized ambulance - Medical Cabinet - 220V AC - Driver/Crew partition - Stretcher platform - Roof mounted ventilator - Interior lighting (LED) - Dual 15 lbs oxygen tank			



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Squad bench with under seat - Non slip heavy duty ambulance grade flooring Self Loading Stretcher with housing for spine board and 10G rated fastener Material: Stainless Steel, Aluminum and Polyethylene Construction: Fully Welded Frame Work Length: 1980mm Width: 585mm Weight: 36kg Loading Capacity: 170kg Wheels: 200mm diameter, fixed front and auto-directed rear - Anti shock position and Trendelenburg - Brakes on rear wheels - Crash assist system SMAX Fastener Specification - Crash Certification: 10G - Dimensions: 1790 x 190 x 80 ± 5mm - Metal profile thickness: 30mm - Materials: AI, Nylon, PE, Steel - Weight: 5.2 ± 0.1 kg Scoop Stretcher - CE Certified - 3 blade design - Material: Aluminum - Loading Capacity: 150 kg - Weight: 7.9kg - Shortened Length: 1660mm - Intermediate Length 1: 1780mm - Intermediate Length 2: 1900mm - Intermediate Length 3: 2050mm - Folded Length: 1190mm - Thickness Folded: 70mm 			



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga

Location of the Project : City Disaster Risk Reduction and Management Office

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Thickness Opened: 70mm - Width: 440mm - 3 pcs belt <p>Spine Board</p> <ul style="list-style-type: none"> - Integrated adult and pediatric - CE Certified - Length: 1830mm - Width: 445mm - Thickness: 60mm - No. of Handles: 14 - Load Capacity: 140kgs - Weight: 9.2kg <p>Adult/ Pedia immobilizer</p> <ul style="list-style-type: none"> - Convertible Adult/ Pedia head immobilizer - CE Certified - Material: PE, Nylon, TPU - Attachments Points: 4 - Dimension: 380 x 265 x 180mm - Cushion specification: with auricle inspections and rigid cushions - Height: 170mm for adult; 125mm for pedia - Total Weight: 2080kg - 2 total strong PE blocks with insertions of a soft, anallergic rubber with large opening for ear inspection adjustable frontal and chin straps - X-ray translucent with floating capability <p>Adult and Pedia Straps</p> <ul style="list-style-type: none"> - Reflective universal straps - CE Certified - Material: Nylon-Polypropylene - Width of Strap: 53mm - V-Tape Length: 250mm (min)/ 520mm (max) - Central Belt Length: 1200 - Weight: 630g - Pedia Strap: CE Certified - Material: Nylon - Central Belt Length: 750mm - Integrated Measuring Tape: 1500mm - Weight: 460g 			



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Sliding Transversal Bands with reflective inserts Transport/ Stair Chair with Four Wheels - CE Certified - Materials: AL, Steel, PU, PVC - Seat/Back Rest Material: double layered anti-scratch polyethylene - Length with closed handles: 710mm - Length with closed handles: 710mm - Length with opened handles: 1080mm - PVC sheets - 2 rear foldable handles - Self positioning foot rest with brakes - 10G Certified with 4BELL MAX 4 Collar Kit - CE Certified - Material: PE, Nylon - Sizes: XS, S, M, L - Weight: 545g - With Bag Blu Splint Pro - Rigid splints with flexible internal structure - CE Certified - Material: Neoprene, AL, Nylon - Flexible moldable aluminum core - Quick release fasteners with buckles Washable up to 40C by removing the inners core Extrication/spine immobilization - CE certified - Dimension: 830mm L x 25mm at thickest point - Belts Length: 74cm - Weight without bag: 2.60kg - Weight with bag: 2.95kg - Loading Capacity: 230kg - Color Coded Belt System - PVC Coated for Easy Sanitation - With Cushion for the nuchal area Traction/immobilization splint 			



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - serrated traction mechanism and “S” shape coupler - supporting feet and ring for the release of the blocking coupler - four padded support straps for the keg - strap and ischial padding - extendable strap for ankle - transport bag - Minimum length (1): 89 0 ± 10 mm - Maximum length (1): 1350 ± 10 mm - Width: 210 m - Base width: 230 mm - Leg support sone width: 165 mm - Traction belt length: from 0 to 500 mm - Slope: 10° (Variable depending on the extension) - Materials: Steel, Al, Nylon Weight: 1,78 ± 0,1 kg <p>Portable suction device with 10G wall fixing with auto recharger</p> <ul style="list-style-type: none"> - CE Certified 10G Compliant - with auto charging wall mount - with fall protection system - Dimensions: 200x225x285 mm - Dimensions with mount: 200 x 250 x 320 mm - Suction device weight: 2.4kg - Mount/Fixation Weight: .8kg - Vacuum Range: from 50 to 555 mmHg - Free flow Suction: 32L/min - Noise level: 70db - Input Voltage: 100-240 VAC 47~63HZ .75Max or 12VDC 33W Max - IP Grade: IP1 - Battery: 12V DC Ni-MH - Operating time: 30 min. On, 30 min. Off - Battery Recharging Time to full Capacity: 5h - Vase Capacity: 1000 ml autoclavable - Patient Tube Length: 1.8m - Operating Temperature : From 0°C to ± 47°C - Storage Temperature: From -40°C to ± 70°C - with UNI EN 1789 certification 			



Republic of the Philippines
Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Compliant with ISO 100079-1 - Automatically recharges once mounted - Standard Accessories: - 10G mount with charging system - Battery - 1000ml autoclavable canister - 1.8m patient tube - Shoulder strap for easy carrying Aneroid sphygmomanometer with large dial and protection and Sprague Rappaport Stethoscope - CE Certified - Material: PE, Nylon, Rubber, AL - Extended cuff dimension: 530x145mm - Rubber protection dimension: 220x150mm - Dial Diameter: 130mm - Pipe length: from 15 to 172cm - Manometer range: 0-300mmHg - Weight: 1.1kg - MD Class Im CE marked according to Dir. 93/42/CEE - Conforms to UNI N ISO 81060 -1 - Highly Visible Dial with Rubber Protection - Spiral connection pipe to sphygmomanometer - Dial with numbering at 20mmHg and division of 2 mmHg - Compartment for housing the cuff accessories - Integrated elastic band in the compartment - DGX 198 Stethoscope - Technical data: - Bell maximum diameter: 45mm - Bell minimum diameter: 31mm - Tubes length: 56 cm - Weight: 235g - Lightweight - With metal clips on both tubing to minimize movement Comes with spare ear tips (2 Big , 2 Small) REGULATOR with HUMIDIFIER GROUP - Chromed brass structure 			



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Inlet filter in sintered bronze - Graded gauge 40 mm diameter with precision class 2,5 - Incoming pressure: 230 bar - Outgoing pressure: adjustable from 0 to 4 bar (pre - fixed 4 bar) - Safety valve pre-fixed - Humidifier Group Specifications: - Technical data - Flowmeter with probe - Dimensions 85x150x35 mm - Nominal pressure 350 kPa - Flow From 0 to 15 l/min - Deliverable gas Oxygen - Materials PC, anodized Al, Brass - Humidifier - Dimensions Ø 70x135 mm - Max. volume 130 ml - Output hose Ø 7mm - Operating pressure 350 kPa - Max flow 20L/min - Materials PC, Al - Overall weight 250 g <p>Oxygen Wall Outlet Specification: Simple and safe use guaranteed by the adoption of the gas specific connection and quick release mechanism Smooth surfaces for an easy cleaning Innovative locking mechanism that allows easy installation Overall dimensions 100x100x115 ±5mm Connection Standard UNI Materials Nylon, Al, Brass Class IIb Med.Device according to Dir. 93/42/CEE</p> <p>STRETCHER BASE</p> <ul style="list-style-type: none"> - High quality base made of stainless steel and aluminum for easy loading and unloading of the stretchers - Technical Data <p>Material: Aluminum, stainless steel</p>			



Republic of the Philippines
Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Inclination angle: 22° - Under storage: 1 spine board or scroop stretcher Load Capacity: 220kg <p>EMERGENCY AUDIO AND VISUAL WARNING SYSTEM</p> <p>FENIEX QUANTUM 2.0 60" LED LIGHT BAR - R/W 1 Set 60 LED EMERGENCY WARNING LIGHTBAR</p> <ul style="list-style-type: none"> - 4 programmable priority flashing moves - Syncs with T3, Cannon, Under Mirror Puck and QSM - Multiple programmable modes: <ul style="list-style-type: none"> - Flood modes - Stop, tail & turn signal patterns - Cruise mode patterns - Traffic advisor modes - Cut-off modes - California Red option - Dim modes - 156x single color led count - 15 programmable flash patterns - Field serviceable - 40° optical light spread for the longrange visibility - 15' cable length - Packaged with Quad Converter Providing 28 programmable nodes - Military-grade aluminum housing - Anti-yellowing & anticracking clear-coated polycarbonate lens - Dimensions: 1.6" H x 11.8"W x 59.8" L - Voltage: 10~18VDC - Current Draw: 16A - 4Certifications: IP66, SAEJ1113, SAEJ595, ECE R65 Class 1 Certified, CT13, NFPA, NFPA KKK, SAE 578, SAE 575, SAE 845 - 1 Year Warranty <p>FENIEX FUSION SURFACE MOUNT WARNING LIGHTS – R</p>			



Republic of the Philippines
Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - 40° optical light spread for long-range visibility - 3 programmable modes - Syncs with T3, Cannon, Under Mirror Puck and QSM - 10' cable length - 6x single color led count - Multiple modes capabilities: - Flood mode patterns - Stop, tail & turn signal patterns - Military-grade aluminum housing - Anti-yellowing & anticracking clear-coated polycarbonate Lens - Voltage: 10~18VDC - Current Draw: 1A - Certifications: ip66, SAEJ1113-11, SAEJ595, ECE R65 CLASS 1 CERTIFIED, CT13, NFPA KKK1 Year WARRANTY <p>FENIEX WIDE LUX 7 X 3 SURFACE MOUNT WARNING LIGHTS – R. Intense perimeter lighting in an ultra-compact, slim design. Extremely functional and customizable, can be used as a brake-tail-turn, reverse, warning light or scene light and steady on capabilities at 50% brightness.</p> <ul style="list-style-type: none"> - Available modes: Brake light mode - Tail light mode - Dim mode - Turn light mode - Front or rear mounting options available - 18x led count - 180° light spread - 10" cable harness - Mounting hardware provided - 20+ flash patterns - Military-grade aluminum housing - Anti-yellowing & anticracking clear-coated polycarbonate Lens - Dimensions: 3.775" x 8" x 1" - Voltage: 10~18VDC - Current Draw: 1A 			



Republic of the Philippines
Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none"> - Certifications: SAEJ1113-11, SAEJ595, NFPA KKK - 1 Year Warranty <p>FENIEX STORM PRO 200W with 2 100W TRITON SPEAKERS</p> <ul style="list-style-type: none"> - SIREN and PUBLIC ADDRESS SYSTEM - STORM PRO 200W Siren Specifications: <ul style="list-style-type: none"> - Up to 130 decibels of clear, thundering sound in programmable tones - Dual-tone capable with remote activation that allows universal compatibility with other controllers - 200W power output - 21 programmable tones - Dual tone capability - Microphone included for PA functionality - Capabilities: <ul style="list-style-type: none"> - Radio rebroadcast - Park-kill - Horn ring - 6 programmable modes - Integrated push button for tone selection - Purchase includes 200W siren, RJ45 cable, microphone and microphone mounting set - Functions with most existing controllers and switch panels - Military-grade aluminum housing (Siren) - Dimensions: 6.6" x 6" x 2.5" - Voltage: 10~18VDC - Current Draw: 20A <p>Certifications: IP67, SAEJ1849, SAEJ1113-11</p> <ul style="list-style-type: none"> - TRITON 100w SPEAKER/SIREN <p>Specifications:</p> <ul style="list-style-type: none"> - Compact low-profile design and durable polycarbonate housing, ideal speaker - for any police, fire, or EMS vehicle - Uniquely engineered to achieve 85 degree sound dispersion - Impedance of 11 ohms - Neodymium magnet 			



Republic of the Philippines

Province of Pampanga

City of San Fernando

Office of the Bids and Awards Committee

REQUEST FOR QUOTATION

(FM-CSFP-CGSO-39; Revision No.03; 04/01/2022)

Project Title : **Supply and Delivery of Response Vehicle (Ambulance) to be used at the City Disaster Risk Reduction and Management Office in the City of San Fernando, Pampanga**

Location of the Project : **City Disaster Risk Reduction and Management Office**

Item No.	Qty	Unit	Item Description	Remarks	Unit Price	Total
			<ul style="list-style-type: none">- Universal compatibility- Built-in l-shaped mounting bracket- Purchase includes 1 Triton Speaker- Compact, slim design to fit behind grille- Lightweight durable polycarbonate frame- Military-grade aluminum housing- Dimensions: 7" x 7" x 3"- Meets or exceeds SAE J1849 standards.- 1 Year Warranty <p>FENIEX 4200 MINI CONTROLLER</p> <ul style="list-style-type: none">- Versatile All Around Compact 6 Button Programmable Controller for Siren and Emergency Lighting- Specifications:- 6 Programmable momentary or on/off buttons- All in one controller with integrated relay- Integrated 2 outputs wigwag function- 6 x 3.5 Amp outputs- LED backlit buttons- Includes two mounting brackets surface mount swivel mount- Universal compatibility- Includes legend sheet <p>Rugged weather-resistant enclosure</p> <ul style="list-style-type: none">- DECALS AND MARKINGS- High quality Tint- Free LTO registration for the first three (3) years			
Total Amount:						

After having carefully read and accepted your General Conditions, I quote you on the item at prices noted above.

Printed Name/ Signature

Tel No./ Cellphone No.

Date

TERMS OF REFERENCE

SUPPLY AND DELIVERY OF RESPONSE VEHICLE (AMBULANCE) TO BE USED FOR THE CITY DISASTER RISK REDUCTION AND MANAGEMENT OFFICE FOR 2025 IN THE CITY OF SAN FERNANDO, PAMPANGA

I.BACKGROUND

Ambulance is a medically equipped vehicle which transports patients to treatment facilities, such as hospitals. Typically, out-of-hospital medical care is provided to the patient.

Ambulances are used to respond to medical and trauma emergencies by San Fernando Rescue Unit (SAFRU) specifically technical rescue that need transport of patient to definitive care. For this purpose, they are generally equipped with flashing warning lights and sirens. They can rapidly transport the personnel and other first responders to the scene, carry equipment for administering emergency care and transport patients to hospital or other definitive care

The San Fernando Rescue Unit (SAFRU) is the response arm of the City of San Fernando Disaster Risk Reduction and Management Division (CDRRMD), the local government's division that is responsible in the continuous journey towards a disaster-resilient locality.

In line with this, SAFRU has been rendering 24/7 medical and rescue services not only to its constituents but also to nearby towns and municipalities. And to be effective, a new emergency vehicle can bring speedy response that must be on the scene within a certain time of the initial emergency call.

II.BUDGETARY REQUIREMENT

The Budgetary Requirement for the Supply and Delivery of Response Vehicle (Ambulance) to be used for the City Disaster Risk Reduction and Management Office for 2025 in the City of San Fernando, Pampanga, is included in the PPMP, which is in the amount of SIX MILLION PESOS (P 6,000,000.00).

III.OBJECTIVES

- To provide pre-hospital care with sufficient and adequate ambulance supplies and equipment available
- To assist injured patients or those with illness to and from the nearest health facility

IV.TERMS AND CONDITIONS

During the procurement process and delivery/ implementation of the contract, the end- user and the supplier/ contractor shall:

- a. Specifications/ Schedule of Requirements

1 (One) Unit Brand New High Roof Ambulance

Overall (LxWxH): 5,915 x 1,950 x 2,280 mm

Wheelbase:3860mm

Engine Type: 2.8L, 4 Cylinders, In-line Type 16-Valve DOHC
Engine Displacement: 2755cc
Maximum Output: 163ps / 3,600rpm
Maximum Torque: 420Nm / 1,400 – 2,200 rpm
Transmission: Dash Mounted, AT
Fuel Capacity: 70L
Tires: 235 / 65 R16C
Wheels: 7J x 16" (Alloy)

Fully customized ambulance

- Medical Cabinet
- 220V AC
- Driver/Crew partition
- Stretcher platform
- Roof mounted ventilator
- Interior lighting (LED)
- Dual 15 lbs oxygen tank
- Squad bench with under seat
- Non slip heavy duty ambulance grade flooring

Self Loading Stretcher with housing for spine board and 10G rated fastener

Material:

Stainless Steel, Aluminum and Polyethylene

Construction:

Fully Welded Frame Work

Length:

1980mm

Width:

585mm

Weight:

36kg

Loading Capacity:

170kg

Wheels:

200mm diameter, fixed front and auto-directed rear

- Anti shock position and Trendelenburg
- Brakes on rear wheels
- Crash assist system

SMAX Fastener Specification

- Crash Certification: 10G
- Dimensions: 1790 x 190 x 80 ± 5mm
- Metal profile thickness: 30mm
- Materials: Al, Nylon, PE, Steel
- Weight: 5.2 ± 0.1 kg

Scoop Stretcher

- CE Certified
- 3 blade design
- Material: Aluminum
- Loading Capacity: 150 kg
- Weight: 7.9kg
- Shortened Length: 1660mm
- Intermediate Length 1: 1780mm

- Intermediate Length 2: 1900mm
- Intermediate Length 3: 2050mm
- Folded Length: 1190mm
- Thickness Folded: 70mm
- Thickness Opened: 70mm
- Width: 440mm
- 3 pcs belt

Spine Board

- Integrated adult and pediatric
- CE Certified
- Length: 1830mm
- Width: 445mm
- Thickness: 60mm
- No. of Handles: 14
- Load Capacity: 140kgs
- Weight: 9.2kg

Adult/ Pedia immobilizer

- Convertible Adult/ Pedia head immobilizer
- CE Certified
- Material: PE, Nylon, TPU
- Attachments Points: 4
- Dimension: 380 x 265 x 180mm
- Cushion specification: with auricle inspections and rigid cushions
- Height: 170mm for adult; 125mm for pedia
- Total Weight: 2080kg
- 2 total strong PE blocks with insertions of a soft, anallergic rubber with large opening for ear inspection adjustable frontal and chin straps
- X-ray translucent with floating capability

Adult and Pedia Straps

- Reflective universal straps
- CE Certified
- Material: Nylon-Polypropylene
- Width of Strap: 53mm
- V-Tape Length: 250mm (min)/ 520mm (max)
- Central Belt Length: 1200
- Weight: 630g
- Pedia Strap: CE Certified
- Material: Nylon
- Central Belt Length: 750mm
- Integrated Measuring Tape: 1500mm
- Weight: 460g
- Sliding Transversal Bands with reflective inserts

Transport/ Stair Chair with Four Wheels

- CE Certified
- Materials: AL, Steel, PU, PVC
- Seat/Back Rest Material: double layered anti-scratch polyethylene
- Length with closed handles: 710mm
- Length with closed handles: 710mm
- Length with opened handles: 1080mm

- PVC sheets
- 2 rear foldable handles
- Self positioning foot rest with brakes
- 10G Certified with 4BELL MAX

4 Collar Kit

- CE Certified
- Material: PE, Nylon
- Sizes: XS, S, M, L
- Weight: 545g
- With Bag

Blu Splint Pro

- Rigid splints with flexible internal structure
 - CE Certified
 - Material: Neoprene, AL, Nylon
 - Flexible moldable aluminum core
 - Quick release fasteners with buckles
- Washable up to 40C by removing the inner core

Extraction/spine immobilization

- CE certified
- Dimension: 830mm L x 25mm at thickest point
- Belts Length: 74cm
- Weight without bag: 2.60kg
- Weight with bag: 2.95kg
- Loading Capacity: 230kg
- Color Coded Belt System
- PVC Coated for Easy Sanitation
- With Cushion for the nuchal area

Traction/immobilization splint

- serrated traction mechanism and "S" shape coupler
- supporting feet and ring for the release of the blocking coupler
- four padded support straps for the leg
- strap and ischial padding
- extendable strap for ankle
- transport bag
- Minimum length (1): 890 ± 10 mm
- Maximum length (1): 1350 ± 10 mm
- Width: 210 mm
- Base width: 230 mm
- Leg support sole width: 165 mm
- Traction belt length: from 0 to 500 mm
- Slope: 10° (Variable depending on the extension)
- Materials: Steel, Al, Nylon

Weight: $1,78 \pm 0,1$ kg

Portable suction device with 10G wall fixing with auto recharger

- CE Certified 10G Compliant
- with auto charging wall mount
- with fall protection system
- Dimensions: 200x225x285 mm

- Dimensions with mount: 200 x 250 x 320 mm
- Suction device weight: 2.4kg
- Mount/Fixation Weight: .8kg
- Vacuum Range: from 50 to 555 mmHg
- Free flow Suction: 32L/min
- Noise level: 70db
- Input Voltage: 100-240 VAC 47~63HZ .75Max or 12VDC 33W Max
- IP Grade: IP1
- Battery: 12V DC Ni-MH
- Operating time: 30 min. On, 30 min. Off
- Battery Recharging Time to full Capacity: 5h
- Vase Capacity: 1000 ml autoclavable
- Patient Tube Length: 1.8m
- Operating Temperature : From 0°C to $\pm 47^{\circ}\text{C}$
- Storage Temperature: From -40°C to $\pm 70^{\circ}\text{C}$
- with UNI EN 1789 certification
- Compliant with ISO 100079-1
- Automatically recharges once mounted
- Standard Accessories:
 - 10G mount with charging system
 - Battery
 - 1000ml autoclavable canister
 - 1.8m patient tube
 - Shoulder strap for easy carrying

Aneroid sphygmomanometer with large dial and protection and Sprague Rappaport Stethoscope

- CE Certified
- Material: PE, Nylon, Rubber, AL
- Extended cuff dimension: 530x145mm
- Rubber protection dimension: 220x150mm
- Dial Diameter: 130mm
- Pipe length: from 15 to 172cm
- Manometer range: 0-300mmHg
- Weight: 1.1kg
- MD Class Im CE marked according to Dir. 93/42/CEE
- Conforms to UNI N ISO 81060 -1
- Highly Visible Dial with Rubber Protection
- Spiral connection pipe to sphygmomanometer
- Dial with numbering at 20mmHg and division of 2 mmHg
- Compartment for housing the cuff accessories
- Integrated elastic band in the compartment
- DGX 198 Stethoscope
- Technical data:
 - Bell maximum diameter: 45mm
 - Bell minimum diameter: 31mm
 - Tubes length: 56 cm
 - Weight: 235g
 - Lightweight
 - With metal clips on both tubing to minimize movement
- Comes with spare ear tips (2 Big , 2 Small)

REGULATOR with HUMIDIFIER GROUP

- Chromed brass structure
- Inlet filter in sintered bronze
- Graded gauge 40 mm diameter with precision class 2,5
- Incoming pressure: 230 bar
- Outgoing pressure: adjustable from 0 to 4 bar (pre - fixed 4 bar)
- Safety valve pre-fixed
- Humidifier Group Specifications:
- Technical data
- Flowmeter with probe
- Dimensions 85x150x35 mm
- Nominal pressure 350 kPa
- Flow From 0 to 15 l/min
- Deliverable gas Oxygen
- Materials PC, anodized Al, Brass
- Humidifier
- Dimensions Ø 70x135 mm
- Max. volume 130 ml
- Output hose Ø 7mm
- Operating pressure 350 kPa
- Max flow 20L/min
- Materials PC, Al
- Overall weight 250 g

Oxygen Wall Outlet Specification:

Simple and safe use guaranteed by the adoption of the gas specific connection and quick release mechanism

Smooth surfaces for an easy cleaning

Innovative locking mechanism that allows easy installation

Overall dimensions 100x100x115 ±5mm

Connection Standard UNI

Materials Nylon, Al, Brass

Class IIb Med.Device according to Dir. 93/42/CEE

STRETCHER BASE

- High quality base made of stainless steel and aluminum for easy loading and unloading of the stretchers

- Technical Data

Material: Aluminum, stainless steel

- Inclination angle: 22°

- Under storage: 1 spine board or scroop stretcher

Load Capacity: 220kg

EMERGENCY AUDIO AND VISUAL WARNING SYSTEM

FENIEX QUANTUM 2.0 60" LED LIGHT BAR - R/W 1 Set 60 LED EMERGENCY WARNING LIGHTBAR

- 4 programmable priority flashing moves
- Syncs with T3, Cannon, Under Mirror Puck and QSM
- Multiple programmable modes:
- Flood modes
- Stop, tail & turn signal patterns
- Cruise mode patterns
- Traffic advisor modes
- Cut-off modes

- California Red option
- Dim modes
- 156x single color led count
- 15 programmable flash patterns
- Field serviceable
- 40° optical light spread for the longrange visibility
- 15' cable length
- Packaged with Quad Converter Providing 28 programmable nodes
- Military-grade aluminum housing
- Anti-yellowing & anticracking clear-coated polycarbonate lens
- Dimensions: 1.6" H x 11.8"W x 59.8" L
- Voltage: 10~18VDC
- Current Draw: 16A
- 4Certifications: IP66, SAEJ1113, SAEJ595, ECE R65 Class 1 Certified, CT13, NFPA, NFPA KKK, SAE 578, SAE 575, SAE 845
- 1 Year Warranty

FENIEX FUSION SURFACE MOUNT WARNING LIGHTS – R

- 40° optical light spread for long-range visibility
- 3 programmable modes
- Syncs with T3, Cannon, Under Mirror Puck and QSM
- 10' cable length
- 6x single color led count
- Multiple modes capabilities:
- Flood mode patterns
- Stop, tail & turn signal patterns
- Military-grade aluminum housing
- Anti-yellowing & anticracking clear-coated polycarbonate Lens
- Voltage: 10~18VDC
- Current Draw: 1A
- Certifications: ip66, SAEJ1113-11, SAEJ595, ECE R65 CLASS 1 CERTIFIED, CT13, NFPA KKK1 Year WARRANTY

FENIEX WIDE LUX 7 X 3 SURFACE MOUNT WARNING LIGHTS – R. Intense perimeter lighting in an ultra-compact, slim design. Extremely functional and customizable, can be used as a brake-tail-turn, reverse, warning light or scene light and steady on capabilities at 50% brightness.

- Available modes: Brake light mode
- Tail light mode
- Dim mode
- Turn light mode
- Front or rear mounting options available
- 18x led count
- 180° light spread
- 10" cable harness
- Mounting hardware provided
- 20+ flash patterns
- Military-grade aluminum housing
- Anti-yellowing & anticracking clear-coated polycarbonate Lens
- DImensions: 3.775" x 8" x 1"
- Voltage: 10~18VDC
- Current Draw: 1A
- Certifications: SAEJ1113-11, SAEJ595, NFPA KKK

- 1 Year Warranty

FENIEX STORM PRO 200W with 2 100W TRITON SPEAKERS

- SIREN and PUBLIC ADDRESS SYSTEM
- STORM PRO 200W Siren Specifications:
- Up to 130 decibels of clear, thundering sound in programmable tones
- Dual-tone capable with remote activation that allows universal compatibility with other controllers
- 200W power output
- 21 programmable tones
- Dual tone capability
- Microphone included for PA functionality
- Capabilities:
- Radio rebroadcast
- Park-kill
- Horn ring
- 6 programmable modes
- Integrated push button for tone selection
- Purchase includes 200W siren, RJ45 cable, microphone and microphone mounting set
- Functions with most existing controllers and switch panels
- Military-grade aluminum housing (Siren)
- Dimensions: 6.6" x 6" x 2.5"
- Voltage: 10~18VDC
- Current Draw: 20A

Certifications: IP67, SAEJ1849, SAEJ1113-11

- TRITON 100w SPEAKER/SIREN Specifications:
- Compact low-profile design and durable polycarbonate housing, ideal speaker
- for any police, fire, or EMS vehicle
- Uniquely engineered to achieve 85 degree sound dispersion
- Impedance of 11 ohms
- Neodymium magnet
- Universal compatibility
- Built-in I-shaped mounting bracket
- Purchase includes 1 Triton Speaker
- Compact, slim design to fit behind grille
- Lightweight durable polycarbonate frame
- Military-grade aluminum housing
- Dimensions: 7" x 7" x 3"
- Meets or exceeds SAE J1849 standards.
- 1 Year Warranty

FENIEX 4200 MINI CONTROLLER

- Versatile All Around Compact 6 Button Programmable Controller for Siren and Emergency Lighting
- Specifications:
- 6 Programmable momentary or on/off buttons
- All in one controller with integrated relay
- Integrated 2 outputs wigwag function
- 6 x 3.5 Amp outputs
- LED backlit buttons
- Includes two mounting brackets surface mount swivel mount

- Universal compatibility
 - Includes legend sheet
- Rugged weather-resistant enclosure

- DECALS AND MARKINGS
- High quality Tint

Other Requirements

- Availability of spare parts all over Luzon, Visayas and Mindanao
- Basic tool kit with set of tools and jack, new spare tire, early warning device, 3m tint and floor matting
- Free LTO registration for the first three (3) years
- Free labor on preventive maintenance service within the first 1,000 and 5,000 kilometer check-up / change oil.
- Copy of the Certificate of Authorized/ Sole Dealership by the Manufacturer/ Distributors, which ever is applicable to the supplier.
- A copy of Service/ Maintenance Manual and Parts Manual
- Manufacturer must have an "After- Sales Service/ Parts Program," and or authorized Dealer/ Distributor must have an access to the manufacturer's "After-Sales Service/ Parts Program," whichever is applicable
- With Service Centers within the province and key cities in the province with the following:
 - Qualified mechanics
 - Availability of Original Manufacturer parts.
- Certificate from the Manufacturer that the brand of the vehicle has been in the local industry (in the Philippines) for at least 30 years, and other supporting documents related hereto

Warranty

Submission of Warranty Certificate which is one (1) year on both parts and labor

b. Procurement Process

1. For the End- user, ensure the completion of the documents in order to proceed with the procurement process.
2. For the supplier/ provider, ensure the completeness of the documents being required by the Bids and Awards Committee (BAC) for the procurement process on- time based on the procurement schedule including this TOR duly signed by the end- user and conformed by the supplier/ contractor.
3. If the procurement process reaches the ensuing year, observe that the allowed delivery is only up to what is stipulated in the contract.
4. For the End- user, present clearly this TOR during the Pre- Bid Conference for the information of the prospective bidder/s (for Competitive/ Public Bidding), and present by the Buyer with the assistance of the End- user (for Alternative Methods of Procurement).

5. Ensure to supply the requirements upon issuance of PO/Contracts. During the post-qualification, the BAC in coordination with the CGSO-Motorpool Division, shall conduct inspection if the lowest Lowest Calculated Responsive Bidder (LCRB) has satisfactorily complied with the specifications and other conditions of the project, and shall serve as basis to proceed with the Notice of Award (NOA)
6. Comply with the provisions of the Procurement Law regardless of the mode of procurement, whether Competitive/ Public Bidding or the use of Alternative Methods of Procurement.

c. Delivery/ Implementation period

1. Strictly observe the "No Purchase Order (PO)/ Delivery Order Contract (DOC), No Delivery" Policy and comply with the delivery period.
2. The Delivery Period shall be from 30 days from the receipt of P.O.
3. During the delivery, strictly follow the provisions enumerated in the Terms and Condition of the PO/ Contract including the Delivery Schedule, Penalty, among others.
4. In case there is a change in the Delivery Schedule and specifications, the End- user through the Procurement Officer shall coordinate with the CGSO- Procurement Management Division (PMD) for the latter to advise the supplier/ contractor regarding the concern.
5. Coordination with the supplier/ contractor shall be the function of the CGSO- PMD as its mandate.
6. For onsite delivery, ensure the coordination with the Inspector from the CGSO- Property and Supply Management Division (PSMD) for the inspection of the delivery in terms of quantity and quality and to immediately notify the supplier/ contractor in case of any concerns before the acceptance.

d. Inspection and Acceptance

1. The CGSO- PSMD in coordination with the CGSO- MPD shall conduct inspection as to the specification including accessories and condition of the vehicle prior to the acceptance. During the delivery, the supplier/ contractor shall provide the following:
 - Certificate of Stock Reported
 - Sales Invoice
 - Stencil of Motor and Chasis Number
 - Picture of the vehicle- four (4) sides
2. Supplier/ Contractor shall be providing the three (3) year LTO Registration for the brand new vehicle

Such documents will be used in notifying the concerned offices on the delivery such as the City Accountant's Office (CAccO) and Commission on Audit (COA) to include the same in the Payables.

V.DELIVERABLES BY THE SUPPLIER/ CONTRACTOR AND THE CITY GOVERNMENT

The deliverables of the supplier/ contractor shall be as follows:

- a. Strictly follow the specifications and timely provision of requirements based on the delivery schedule.

The deliverables of the City Government shall be as follows:

- a. On- time payment of the supplier/ contractor i.e., 15 days after the delivery.
- b. End- user shall monitor the delivery of requirements.
- c. The Procurement Officer shall assist in the monitoring, delivery and on- time payment of the supplier.
- d. Provide necessary and readily- available documents such as during the conduct of post- audit.
- e. Evaluate the performance of the supplier/ contractor and in case there is a violation to the Contract/ Agreement, prepare a Verified Report.

Prepared and submitted by:

Raymond B. Del Rosario
City DRRM Officer

CONFORME:
_____ Signature over Printed Name
_____ Date

Note: *This TOR shall form part of the Contract and should be strictly followed by both parties otherwise, the implementation of the project/ program might be affected as well as the performance of the supplier/ contractor.*